

**SPECIFICATIONS :**

**Structure**

- Utilises Eight Pos Die Cast Grade LM12 Aluminium Alloy Angle Joints
- Complete Knock Down System (FULLY CKD)
- No Welding Require
- Sheet Metal Sections Are Formed Using Thickness 1.5mm Without Sharp Edge
- Assembly Utilises High Quality M8 And M6 Socket Head Cap Screws

**Cover And Door**


- Sheet Metal Sections Are Formed Using Thickness 1.2mm Without Sharp Edge

**Finishing**


- Epoxy Powder Coating
- Thickness Coating 50 - 60 Microns
- Semi Matt Texture Finish

**Colours**


- Dark And Light Grey
- Two Tone




**PLAN VIEW**



**FRONT VIEW**



**SIDE VIEW**



**REAR VIEW**

<b>BRAND.</b>	<b>TOP RACK</b>	<b>SURFACE PREPARATION</b>	<b>UNIT</b>
<b>MODEL.</b>	TRB600/46L O/600/MS	<b>FREE OF OIL &amp; GREASE</b>	<b>MM</b>
<b>STANDARD.</b>	19" MOUNTING	<b>MATERIAL</b> 1.5MM & 1.2MM THK CR SHEET	<b>SCALE</b> N.T.S
<b>MADE IN.</b>	MAYASIA	<b>FINISH</b> TEXTURE	<b>REV</b> 0
		<b>COLOURS</b> DARK & LIGHT GREY	<b>DRAWN</b> ALEX LIM



**YSE INDUSTRIES SDN. BHD.**  
 330879-P  
 NO. 14, JLN ETARID US16, SEKSYEN US,  
 40150 SHAH ALAM, SELANGOR, MALAYSIA.  
 TEL: +603-7847 2292 F.AX: +603-7847 2522  
 e-mail: [opnrc@ysc.com.my](mailto:opnrc@ysc.com.my)  
<http://www.ysc.com.my>